

DCW-40T5

powered by:



CUMMINS 4BT3.9-G2

40KVA|50Hz

Diesel Genset Features

P.F=0.8 3Phase

Generating Set Performance		50Hz	
Service		Prime Power	Standby Power
@50Hz	kVA	40	44
@50Hz	kW	32	35
Rated Speed	r.p.m	1500	
Available Voltages	V	V 400/230 - 416/240 - 440/254 - 460/265 - 600/346 V	
Rated at power factor	0.8	0.8	

Ambient conditions of reference: 1000 mbar, 25°C, 30% relative humidity. Power according to ISO 3046 normative.

GTL Company was certified by TUV ISO9001 for design and manufacture diesel generator

GTL Gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2006/95/EC Low voltage.
- 2004/108/CE Electromagnetic compatibility.
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- EN 12100, EN 13857, EN 60204

Engine Specifications 1.500 r.p.m.

Prime Mover Performance		
Engine Model		CUMMINS 4BT3.9-G2
Rated output	kW	36
4 stroke Diesel Engine - Injection type		Direct
Aspiration type		Turbocharged
Cylinders,number and arrangement		L4
Bore×Stroke	mm	102X120
Total Displacement	L	3.9
Cooling system		WATER
Coolant Capacity-Engine Only	L	7.2
Lube oil specifications		ACE A3 - A5
Specific fuel consumption(at full load)	(L/h)	9.3
Specific oil consumption(at full load)	(L/h)	N.A
Compression Ratio		17.3:1
Speed Governor Type	Type	BYC A / Electronic

P.R.P. Prime Power - ISO 8528:

PRIME POWER is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year,

between stated maintenance intervals.The permissible average power output during a 24 hours period shall not exceed 80% of the prime power.

10% overload available for governing purposes only.

STANDBY POWER (ISO 3046 Fuel Stop power):

Power available for use at variable loads for limited annual time (500h), within the following limits of maximum operating time: 100% load 25h per year

90% load 200h per year. No overload available. Applicable in case of failure of the main in areas of reliable electrical network.

Alternator Specifications 1.500 r.p.m.

Alternator Data		
Model		GTL GS184E13
Output	kW/kVA	32/40
Poles	num	4
Winding Leads		12
Winding Conections (standard)		Standard
Insulation System	class	Class H
Protection		IP23
Coating Type		Standard
Short Circuit Current Capacity		300%
AVR-Standard		SX460
Voltage Regulation	%	±1%
Winding Pitch		2/3
Overspeed	min ⁻¹	2250
Excitation System		SELF-EXCITED
Electrical Features	TDF / THC	NO LOAD < 1.5%, NON-DISTORTING BALANCED LINEAR LOAD < 5.0%
	TIF	<50
	THF	<2%

▶ Generating Set Installation Date

EXHAUST SYSTEM

Max. exhaust temperature at full load	℃	463
Exhaust gas flow	Litre/sec.	101
Maximum allowed back pressure	kPa	10

ELECTRIC STARTING SYSTEM


Battery Charging System, Negative Groud	Ampere	63/40
Crankig Motor	Volt	12/24

LUBRICATION SYSTEM

Minimum Required Lube System Capacity - Sump Plus Filters	L	10.9
Maximum Oil Temperature	℃	121

▶ Standard Control System

COMAP AMF 9



- ▶ Stand-by and prime-power application in one unit
- ▶ 5 languages in the controller & Translator functionality
- ▶ ECU support & Tier 4 Final ready
- ▶ Power over USB for controller's adjustment
- ▶ Fuel Pump control
- ▶ Alarms and gen-set status assignable to binary outputs
- ▶ Run Hours source ECU or internal
- ▶ Possibility to disable protections
- ▶ Start on low battery (only for native prime-power configuration)

▶ Standard Configuration & Option

Item	Standard	Option
Engine	Standard air filter	Heavy duty air filter
	Standard fuel filter	Air intake shutoff valve chawin type
	Standard oil filter	Intake air heater
	Low coolant level sensor	Oil temperature sensor
	Exhaust gases compensator	Diesel-powered heater
	24V Electrical system	Engine water heater
	Radiator with bloweing fan	
	Electronic governor	
	Sender WT	
	Sender OP	
	Hot components and radiator guards	
Alternator	Mobile components guards	
	Self-excited and Self-regulated	Air inlet filter
	IP23 protection degree	IP44/IP54/IP55
	Insulation H class	Space heater/anti-condensation heater
		Environment protection
		Temperature detectors
Electrical system		Parallel operation
	Battery isolator switch	Distribution board with sockets kit and power busbar
	3 poles circuit breaker	4 poles circuit breaker
	Door opening alarm	Adjustable ELCB (Earth Fault)
	Battery charger 220-240V	Grouding rod
Accessories		ATS
	Water separator filter	Diverter valve kit for external fuel tank
	Low fuel level alarm	Automatic fuel refilling kit
	Oil extraction pump	Trailer
	Tool kit for maintenance	Residential silencer
	Voltage/Speed potentiometer	Electric engine fuel heater
	No Expansion tank	Expansion tank for coolant water

Generating Set transport data

Dimensions(Open Skid Type) With Standard Fuel Tank



Over All Size

Length	mm	1700
Height	mm	1360
Width	mm	860

Shipping Volume	m3	1.99
Dry Weight	Kg	900
Fuel Tank Capacity	L	100

- ✓ The complete gen-set is mounted as whole on a heavy-duty fabricated;
- ✓ Anti-vibration pads are fixed between the engine/ alternator feet and the base frame ;
- ✓ The generating set can be lifted or carefully pushed / pulled by the base frame;
- ✓ Dial type fuel gauge and drain plug on the fuel tank;
- ✓ Forklift pockets within base frame (up to 500kVA);

Dimensions(Silent Type) With Standard Fuel Tank



Over All Size

Length	mm	2250
Height	mm	1750
Width	mm	1060

Shipping Volume	m3	4.17
Dry Weight	Kg	1300
Fuel Tank Capacity	L	100

- ✓ All canopy parts are designed with modular principles
- ✓ Without welding assembly
- ✓ Doors on each side
- ✓ All metal canopy parts are painted by electrostatic
- ✓ Polyester powder paint

*** The weights are approximate.**


GTL reserve the right of modify any characteristic without prior notice.

Weights and dimensions based on products standard and dry/illustrations may include optional equipment.

Technical date here described correspond with the available information at the moment of printing.

Industrial design under patent.

Local distributor



Factory: 1# Building, No.8 Tonghong Road , Tongan Industry Zone, Tongan District, Xiamen, China

Head office: 2/F., No. 320, Tongji South Road,

Ji Mei District, Xiamen, China

Tel: +86 0592 7196398 Fax +86 0592 7898663 vicsun@cngtl.com www.cngtl.com

XIAMEN GTL POWER SYSTEM CO.,LTD